

Wall Light / Wall Pack / PD-CH-WPK



Waterproof low-profile LED wall light. Ideal for facades, perimeters, stairs, loading docks and others.

Aluminium housing, powder-coated finish with a choice of polycarbonate or glass lenses. Efficiency with low energy consumption.

Model	PD-CH-WPK-W60	PD-CH-WPK-W120
-------	---------------	----------------

Power	30 W – 40 W – 50 W – 60 W selectable	80 W – 100 W – 120 W selectable
Lumens	120 lm/W	
Input voltage	AC 100 – 277 V / AC 200 – 480 V	
Beam angles	110° / 130°	
IRC	> 75 Ra	
CCT	4000 K / 5000 selectable	3000 K et 5700 K on demand
Driver	Epistar 2835 SMD	
Light source	S05EN	
Power factor	0,95	
Distorsion	< 10 %	
Overvoltage protection	2 Kv	
Operating temperature	-30 °C ~ +50 °C	
Dimming options	0 - 10 V	
IP	IP65	
Service life	50 000 h	
Dimensions	332 x 235,5 x 172 mm	
Weight	4 kg	
Warranty	5 years	
Colour	Bronze	
Materials	Polycarbonate lens (glass lens on demand)	



lighting solutions
solutions d'éclairage

1435, chemin Saint-Armand
Saint-Armand (Québec)
J0J 1T0 Canada

(514) 433.3386
www.purplelighting.com
info@purpledistribution.com