

Panel / Flat backlit panel / PD-CH3135



New arrangement of LEDs installed on a back panel to promote heat dissipation and uniform illumination without yellowing.

With low maintenance costs, this high-quality light source is energy efficient.

Model	PD-CH3135-30W (1 x 4 pi)	PD-CH3135-30W (2 x 2 pi)	PD-CH3135-40W (2 x 4 pi)
-------	--------------------------	--------------------------	--------------------------

Power	30 W	30 W	40 W
Lumens	3,750 lm	3,750 lm	5,000 lm
Input voltage	AC 120 – 277 V		
Beam angles	120°		
IRC	80		
CCT	3,000K / 5,000K		
LED quantity	64 LED	56 LED	84 LED
Light source			
Tube material	Aluminium		
Power factor	0.9		
Distorsion	≤ 20%		
Overvoltage protection	1.5 kV		
Operating temperature	-20°C ~ +45°C		
IP	IP20		
Service life	50,000 h		
Dimensions	1 x 4 ft	2 x 2 ft	2 x 4 ft
Weight			
Warranty	5 Years		
Colour	White		
Accessories	Dimmer 1-10V		



lighting solutions
solutions d'éclairage

1435, chemin Saint-Armand
Saint-Armand (Québec)
J0J 1T0 Canada

(514) 433.3386
www.purrrplelighting.com
info@purrrpledistribution.com